

## **Class B: 4x4 Modified Street Stock Gas - 5800# and 6500#**

*Street legal trucks with performance enhancing parts added.*

- See All General Truck Pull Rules
- See All Class A Stock Rules
- Front weights allowed (60" maximum from center of front axle). Weights must must securely fastened
- Aftermarket parts such as headers, intake manifolds, power chips, camshafts, and other internal engine parts allowed.
- Driveshaft loops or safety chains required.
- Maximum 514 cubic inch limit
- Stock altered frame allowed. No tube chassis. All suspension must be in place.
- Single four barrel carburetor only. Must have choke tower. No dominators or predators allowed. 850 CFM maximum.
- No aluminum cylinder heads unless factory OEM. 2 valves, 1 spark plug, per cylinder. No turbochargers, superchargers, blowers or multiple turbo's.
- 26" hitch height maximum. Hitch 36 - 48" maximum behind center of rear axle. Hitch point minimum of 5" behind bumper.
- Must have working fire extinguisher and kill switch. Driver must wear helmet and wear seat belt. Driver must stay inside cab at all times. Recommended safety equipment: fire suit, bumper, bumper bars, scatter blanket, balancer/front pulley cover and steel flywheel.
- No tunnel ram intake manifold. No alcohol fuel. No pressurized fuel.
- Blocking of rear suspension and ladder bars allowed.
- Truck will be inspected. Trucks not meeting all rules will be disqualified.